

Model Number	A	B	C	D	E	F	G	H	Top In/Out	Front Side	Rear Side
G50-98	62-3/4	57-1/8	22-1/2	22-5/8	5	50-1/2	1/2	15	1	1-1/2	1-1/2
G75-125	65-1/2	61	26-1/4	25	5	56	3/4	20	1-1/2	1-1/2	1-1/2
G82-156	68-13/16	64	26-1/4	25	6	58-5/8	3/4	20	1-1/2	1-1/2	1-1/2
G37-160	48-1/4	43-3/8	26-1/4	25	6	37-5/8	3/4	20	1-1/2	1-1/2	1-1/2
G76-180	68-13/16	64	26-1/4	25	6	58-5/8	3/4	20	1-1/2	1-1/2	1-1/2
G76-200	68-13/16	64	26-1/4	25	6	58-5/8	3/4	20	1-1/2	1-1/2	1-1/2
G91-200	76-5/16	71-13/16	26-1/4	30-5/8	6	66-3/8	3/4	20	1-1/2	1-1/2	1-1/2
G100-200	73-1/16	66-1/8	30-1/4	23-1/4	6	57-1/2	3/4	23	1-1/2	2	2
G72-250A	71-1/16	64-1/2	26-1/4	25	6	58-5/8	3/4	20	1-1/2	1-1/2	1-1/2
G100-250A	73-1/4	66-1/8	30-1/4	23-1/4	6	57-1/2	3/4	23	1-1/2	2	2
G100-270A	73-7/8	66-1/8	30-1/4	23-1/4	6**	57-1/2	3/4	23	1-1/2	2	2
G72-300A	71	64-1/8	26-1/4	25	8	58-5/8	3/4	20	1-1/2	1-1/2	1-1/2
G91-300A	78-7/16	72-5/16	26-1/4	30-5/8	8	66-3/8	3/4	20	1-1/2	1-1/2	1-1/2
G100-310A	75	68-1/2	30-1/4	32-1/4	7	61-3/4	3/4	23	1-1/2	2	2
G65-360A	70-11/16	64-1/2	26-1/4	25	8	58-5/8	3/4	N/A	N/A	1-1/2	1-1/2
G65-400A	70-11/16	64-1/2	26-1/4	25	8	58-5/8	3/4	N/A	N/A	1-1/2	1-1/2
G85-400A	78-13/16	72-5/16	26-1/4	30-5/8	10	66-3/8	3/4	20	1-1/2	1-1/2	1-1/2
G100-400A	76	68-1/2	30-1/4	32-1/4	8	61-3/4	1*	23	1-1/2	2	2
G77-500A	83	76-3/8	26-1/4	33-1/8	10	68-7/8	1*	N/A	N/A	1-1/2	1-1/2
G77-600A	84-15/16	76-3/8	26-1/4	33-1/8	12	68-7/8	1*	N/A	N/A	1-1/2	1-1/2

All Dimensions Shown in Inches

*3/4" for L.P. Models. **7" Vent for L.P. Model. Increase Height 3-5/8" for NSF Models. All Models Require a 120V Power Source.

A Suffix Indicates ASME Tank Construction Available.

