

Model Number	Input BTU/Hr.	60°	70°	80°	90°	100°	Min. to Rec. Contents	Approx. Shipping Weight
G50-98	98,000	158	136	119	106	95	32	270 lbs.
G75-125	125,000	202	173	152	135	121	37	480
G82-156	156,000	252	216	189	168	151	33	490
G37-160	160,000	259	222	194	172	155	14	390
G76-180	180,000	291	249	218	194	175	26	540
G76-200	199,900	323	277	242	215	194	24	540
G91-200	199,900	323	277	242	215	194	28	600
G100-200	199,900	323	277	242	215	194	31	780
G72-250A	250,000	404	346	303	269	242	18	590
G100-250A	250,000	404	346	303	269	242	25	795
G100-270A	270,000	436	374	327	291	262	23	805
G72-300A	300,000	485	416	364	323	291	15	590
G91-300A	300,000	485	416	364	323	291	19	610
G100-310A	310,000	501	429	376	334	301	20	770
G65-360A	360,000	582	499	436	388	349	11	640
G65-400A	399,900	646	554	485	431	388	10	640
G85-400A	399,900	646	554	485	431	388	13	640
G100-400A	399,900	646	554	485	431	388	15	770
G77-500A	500,000	808	693	606	539	485	10	710
G77-600A	600,000	945	810	709	630	567	8	780

Features:

Thermal Efficiency – 80%

Temperature and Pressure Relief Valve – AGA rated and factory installed.

Hand-Hold Cleanout – For removal of lime/sediment deposits.

Gas Control System – Fully adjustable thermostat from 100°F to 180°F, 24 volt combination gas valve includes main gas pressure regulation, On-Off manual valve, 120/24 volt transformer, and high limit temperature cut-out.

Dielectric Nipples – Factory supplied for easier installation.

Limited Warranty

This product features a three year limited warranty against tank leaks. Please refer to Commercial Warranty Information brochure for complete warranty information.