



Designed With You In Mind.™

SEALED-COMBUSTION GAS-FIRED WATER HEATERS 100,000 BTU/HR. THRU 199,000 BTU/HR.



RHEEM-RUUD AdvantagePlus™ Gas

Commercial Water Heaters are specifically designed to provide customers with maximum savings on operation, space and installation. Designed with the most advanced technology available, these products optimize efficiency and operating reliability.

Construction Features:

- 316L stainless steel construction.
- Thermal efficiency of 95% greatly reduces operating costs.
- No burning pilot light.
- Low NO_x emissions.
- 2" polyurethane foam insulation.
- Less than 1/2 degree per hour heat loss (R17).
- Corrosion resistant, high efficiency 90/10 cupronickel heat exchanger.
- Self-diagnostic electronic control featuring digital readout of water temperature set point and differential.
- 70°–160° (180° F temperature setting only available on HE45-160 and HE45-199 booster models).
- Easily accessible front access cover to equipment (24" service clearance recommended).
- Zero clearance to any combustible surface.
- 85 equivalent feet of vent length.
- Booster installation kit provided with HE45-160 and HE45-199 booster models.

Certifications and Ratings:

- The water heaters are UL/ULC listed and exceed the minimum efficiency requirements of ASHRAE/IES 90.1b-1992. All water heaters are supplied with an AGA/ASME rated temperature and pressure relief valve. The control panel is an integrated solid state temperature and ignition control device with integral diagnostics, LED fault display capability and a digital display of temperature settings.

CERTIFIED FOR A 150 PSI MAXIMUM WORKING PRESSURE.