




Standard Features:

- Porcelain enamel lined tank
- Heavy duty anode rods
- ASME construction available
- 2" of rigid foam insulation
- Baked enamel steel jacket
- 5 year limited warranty



These models exceed the minimum efficiency requirements of ASHRAE Standard 90.1b-1992 (Part of the Federally mandated Energy Policy Act (EPact)).

DIMENSIONAL INFORMATION (DIMENSIONS SHOWN IN INCHES)								
MODEL NUMBER	A	B	C	D	WATER CONNECTIONS		APPROX. WEIGHT (LBS.)	
					TOP OUTLET	FRONT SIDE	STANDARD	ASME
					ST80(A)	58-5/16	24-3/16	13-3/16
ST120(A)	59-1/4	28-1/4	11-1/16	4-1/16	2	2	300 lbs.	340 lbs.
ST175(A)	67-1/4	32-1/4	12-9/16	5-9/16	2-1/2	2-1/2	600 lbs.	600 lbs.



APPROXIMATE WIDTH REQUIRED FOR MANIFOLDED STORAGE TANKS (DIMENSIONS SHOWN IN INCHES)			
MANIFOLD TYPE	ST80(A) (WITH FACTORY MANIFOLDS)	ST120(A) (WITH FACTORY MANIFOLDS)	ST175(A)
DUPLEX	54	58	66
TRIPLEX	82	87	102
QUADRUPLEX	108	116	137

TANK INFORMATION			
MODEL NUMBER	TANK CAPACITY (GALLONS)	MAXIMUM WORKING PRESSURE	
		STD.	ASME
ST80(A)	80	150 PSI	125 PSI
ST120(A)	115	150 PSI	160 PSI
ST175(A)	175	150 PSI	150 PSI

